

Standard LMR Cables

Part Number	Application	Cable OD (in)	Cable OD (mm)	Jacket	Jacket Color	Weight LB/FT	Weight KG/M	Operating Temperature Range (F)	Operating Temperature Range (C)	Bending Moment (FT-LB)	Bending Moment (mm)
LMR@-195	Outdoor	0.195	4.95	PE	Black	0.021	0.03	-40/+185	-40/+185	0.2	0.27
LMR@-195-FR	Indoor/Outdoor Riser CMR	0.195	4.95	FRPE	Black	0.021	0.03	-40/+185	-40/+185	0.2	0.27
LMR@-240	Outdoor	0.24	6.1	PE	Black	0.034	0.05	-40/+185	-40/+185	0.25	0.34
LMR@-240-FR	Indoor/Outdoor Riser CMR	0.24	6.1	FRPE	Black	0.034	0.05	-40/+185	-40/+185	0.25	0.34
LMR@-300	Outdoor	0.3	7.62	PE	Black	0.055	0.08	-40/+185	-40/+185	0.38	0.52
LMR@-300-FR	Outdoor	0.3	7.62	FRPE	Black	0.055	0.08	-40/+185	-40/+185	0.38	0.52
LMR@-400	Outdoor	0.405	10.29	PE	Black	0.068	0.1	-40/+185	-40/+185	0.5	0.68
LMR@-400-FR	Indoor/Outdoor Riser CMR	0.405	10.29	FRPE	Black	0.068	0.1	-40/+185	-40/+185	0.5	0.68
LMR@-600	Outdoor	0.59	14.99	PE	Black	0.131	0.2	-40/+185	-40/+185	2.75	3.73
LMR@-600-FR	Indoor/Outdoor Riser CMR	0.59	14.99	FRPE	Black	0.153	0.2	-40/+185	-40/+185	2.75	3.73

Ultraflex LMR Cables

Part Number	Application	Cable OD (in)	Cable OD (mm)	Jacket	Jacket Color	Weight LB/FT	Weight KG/M	Operating Temperature Range (F)	Operating Temperature Range (C)	Bending Moment (FT-LB)	Bending Moment (mm)
LMR@-240-UF	Indoor/Outdoor	0.195	4.953	TPE	Black	0.034	0.05	-40/+185	-40/+185	0.125	0.17
LMR@-400-UF	Indoor/Outdoor	0.405	10.29	TPE	Black	0.405	10.29	-40/+185	-40/+185	0.375	0.51
LMR@-600-UF	Indoor/Outdoor	0.59	14.99	TPE	Black	0.165	0.25	-40/+185	-40/+185	1.75	2.37

75 Ohm LMR Cables

Part Number	Application	Cable OD (in)	Cable OD (mm)	Jacket	Jacket Color	Weight LB/FT	Weight KG/M	Operating Temperature Range (F)	Operating Temperature Range (C)	Bending Moment (FT-LB)	Bending Moment (mm)
LMR@-240-75	Indoor/Outdoor	0.24	6.1	PE	Black	0.034	0.05	-40/+185	-40/+185	0.25	0.34
LMR@-400-75	Indoor/Outdoor	0.405	10.29	PE	Black	0.068	0.1	-40/+185	-40/+185	0.5	0.68
LMR@-600-75	Indoor/Outdoor	0.59	14.99	PE	Black	0.131	0.2	-40/+185	-40/+185	2.75	3.73